



1J5-G

1J5-G

POWER AMPLIFIER PENTODE

Filament	Coated	
Voltage	2.0	d-c volts
Current	0.12	amp.
Maximum Overall Length		4-5/8"
Maximum Seated Height		4-1/16"
Maximum Diameter		1-13/16"
Bulb		ST-14
Base		Medium Shell Octal 7-Pin
Pin 1 - No Connection		Pin 5 - Grid
Pin 2 - Filament +		Pin 7 - Filament -
Pin 3 - Plate		Pin 8 - No Connection
Pin 4 - Screen		
Mounting Position	Vertical, Base Down [◇]	

AMPLIFIER

Plate Voltage	135 max.	volts
Screen Voltage	135 max.	volts
<i>Typical Operation and Characteristics - Class A₁ Amplifier:</i>		
Plate	135	volts
Screen	135	volts
Grid	-16.5	volts
Plate Cur.	7.0	ma.
Screen Cur.	2.0	ma.
Plate Res.	105000 approx.	ohms
Transcond.	950	μmhos
Load Res.	135000	ohms
Power Output	0.45	watt

[◇] Horizontal operation permitted if plane of filament is vertical.

July 1, 1941

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

TENTATIVE DATA